13:42:47h

Datasheet - NWS21.1

S SCHMERSAL

Command and signalling devices / Push buttons and pilot lights - "N" Program / NWS - Selector switch



(Minor differences between the printed image and the original product may exist!)

Ordering details

Product type description Article number EAN code NWS21.1 1164774 4250116200351

Approval

Approval



Global Properties

Product name	NWS - Wahlschalter
Standards	IEC/EN 60947-1, EN 60947-5-1
Suitable for safety functions (Y/N)	No
Mounting	mounting flange
Materials	
- Material of the operators	ABS
- Material of the front ring	ABS, Chromium-plated
Design	Selector switch - Front plate mounting
Color	
- Colour of the handle	Grey
- Colour of the front ring	Silver
Weight	35 g

Manner of using	
Can be illuminated (Y/N)	No
Version knob	long

Mechanical data

Number of switch positions	2 piece
Latching (Y/N)	Yes
Unlocking type	Rotating unlatcher
Probing possible (Y/N)	No
Latching position	right
switching angle	right, 70°
Number of plunger	1
Front plate thickness	
- min. front plate thickness	1.5 mm
- max. front plate thickness	6 mm
Tightening torque for fixing screws	0,6 Nm

Ambient conditions

Ambient temperature	
- Min. environmental temperature	0 °C
- Max. environmental temperature	+80 °C
Storage and transport temperature	
- Min. Storage and transport temperature	-
- Max. Storage and transport temperature	-
Fully insulated (Y/N)	Yes
Sealing type	membrane, lip seal
Protection type IP	IP67, IP69K

LED switching conditions display

- With integrated LED (Y/N)	No
LED switching conditions display	

Dimensions

Dimensions	
- Height	11 mm
Length of the handle	46 mm
- diameters for the actuating heads	Ø 44.5 mm
- Hole, diameter	22.3 mm + 0,4 mm
Spacing	50 x 50 mm

Images

K.A. Schmersal GmbH, Möddinghofe 30, D-42279 Wuppertal The data and values have been checked throroughly. Technical modifications and errors excepted. Generiert am 28.01.2011 - 13:42:47h Kasbase 1.4.0 DBI