



SPECIFICATIONS

Plain lever actuator with frame to fit V3 type micro switch. Supplied with one flexible insulating sheet and two M3 x 20 mm screws with lock washers and nuts. Use the screws both to mount frame to the switch and to mount the complete assembly to the application.

Lever ratio 4.4:1.

Suitable for plunger actuated micro switches for Series MV 25 and MV 27.

MATERIAL

- Frame (Bracket) : Stainless Steel (1 no.).
- Plain Lever : Stainless steel (1 no.).
- Lock washers : Spring steel (2 nos.).
- Screws : MS, Zinc plated, white passivation, (2 nos.).
- Nuts : MS, Zinc plated, white passivation (2 nos.).
- Flexible Insulator : Rubber coated Nylon fabric (1 no.).

CAT. No. : HL11

ISS.	DATE	MODIFICATION	SIGN.
------	------	--------------	-------

TOLERANCES UNLESS OTHERWISE SPECIFIED ± 0.1	PLAIN HINGED LEVER ACTUATOR SUITABLE FOR MICRO SWITCHES SERIES : MV25 & MV27	DIMENSIONS IN MM	
		DATE	SIGN.
SCALE 1:1 		DESIGN	26.05.12
		DRAWN	26.05.12
		CHKD.	
		APPD.	
	ESSEN DEINKI 22, INDUSTRIAL AREA, PHASE II CHANDIGARH - 160002	DRG. NO. MV25CU-078.	A4
		SHEET 01 OF 01	

C8\PRODUCTSCAN\catalogue_june-04\MV25--SERIES\MV25CU