

**SPECIFICATIONS**

Lever actuator with free running roller. Supplied with frame to fit on one V3 type switch, a flexible insulating sheet and two M3 x 20 mm screws with washers and nuts. Use the screws both to mount frame to the switch and to mount the complete assembly to the application. Lever ratio 4:1.




Suitable for plunger actuated micro switch in the  
 MV 25 Series,  
 MV 27 Series.

**MATERIAL**

- Frame (Bracket) : Stainless Steel (1 no.).
- Roller Lever : Stainless steel (1 no.).
- Roller : Nylon (1 no.).
- Lock washers : Springsteel (2 nos.).
- Screws : MS, Zinc plated, white passivation, (2 nos.).
- Nuts : MS, Zinc plated, white passivation (2 nos.).
- Flexible Insulator : Rubber coated Nylon fabric (1 no.).

**CAT. No. : HR13**

ISS.	DATE	MODIFICATION	SIGN.

TOLERANCES UNLESS OTHERWISE SPECIFIED $\pm 0.1$	<b>ROLLER LEVER ACTUATOR</b> SUITABLE FOR MICRO SWITCH SERIES : MV25 & MV27	DIMENSIONS IN MM		
			DATE	SIGN.
SCALE 1:1 	 <b>ESSEN DEINKI</b> 22, INDUSTRIAL AREA, PHASE II CHANDIGARH - 160002	DESIGN	19.04.12	
		DRAWN	19.04.12	
		CHKD.		
		APPD.		
		DRG. NO.	MV25CU-077. A4	
		SHEET 01 OF 01		

C8\PRODUCTSCAN\catalogue\_june-04\MV25-SERIES\MV25CU