

SPECIFICATIONS

Plain lever actuator, supplied with frame to fit on one V3 type micro switch, an insulating sheet and two M3 x 20 mm screws with lock washers and nuts. Use the screws both to mount the frame to the switch and to mount the complete assembly to the application.  
Lever ratio 4.4:1.

Suitable for plunger actuated micro switches in the Series MV 25 and MV 27.

MATERIAL

- Frame (Bracket) : Stainless Steel (1 no.).
- Plain Lever : Stainless steel (1 no.).
- Lock washers : Spring steel (2 nos.).
- Screws : MS, Zinc plated, white passivation, (2 nos.).
- Nuts : MS, Zinc plated, white passivation (2 nos.).
- Flexible Insulator : Rubber coated Nylon fabric (1 no.).


CAT. No. : HL13

ISS.	DATE	MODIFICATION	SIGN.

TOLERANCES  
UNLESS  
OTHERWISE  
SPECIFIED  
 $\pm 0.1$

PLAIN HINGED LEVER ACTUATOR  
SUITABLE FOR MICRO SWITCHES  
SERIES : MV25 & MV27

DIMENSIONS IN MM		
	DATE	SIGN.
DESIGN	22.08.12	
DRAWN	22.08.12	
CHKD.		
APPD.		



**ESSEN DEINKI**  
22, INDUSTRIAL AREA, PHASE II  
CHANDIGARH - 160002

DRG. NO.  
MV25CU-080. A4  
SHEET 01 OF 01

C8\PRODUCTSCAN\catalogue\_june-04\MV25-SERIES\MV25CU