

**SPECIFICATIONS**

Extended lever actuator, supplied with frame to fit on one V3 type micro switch, an insulating sheet and two M3 x 20 mm screws with lock washers and nuts. Use the screws both to mount the frame to the switch and to mount the complete assembly to the application.  
Lever ratio 13.6:1.



Suitable for plunger actuated micro switches in the Series MV 25 and MV 27.

**MATERIAL**

- Frame (Bracket) : Stainless Steel (1 no.).
- Extended Lever : Stainless steel (1 no.).
- Lock washers : Spring steel (2 nos.).
- Screws : MS, Zinc plated, white passivation, (2 nos.).
- Nuts : MS, Zinc plated, white passivation (2 nos.).
- Flexible Insulator : Rubber coated Nylon fabric (1 no.).

CAT. No. : HL14

ISS.	DATE	MODIFICATION	SIGN.
------	------	--------------	-------

TOLERANCES UNLESS OTHERWISE SPECIFIED $\pm 0.1$	EXTENDED HINGED LEVER ACTUATOR SUITABLE FOR MICRO SWITCHES SERIES : MV25 & MV27	DIMENSIONS IN MM		
			DATE	SIGN.
		DESIGN	19.11.12	
		DRAWN	19.11.12	
		CHKD.		
		APPD.		
SCALE 1:1	 <b>ESSEN DEINKI</b> 22, INDUSTRIAL AREA, PHASE II CHANDIGARH - 160002	DRG. NO. MV25CU-087. A4		
		SHEET 01 OF 01		

C:\PRODUCTSCAN\catalogue\_june-04\MV25-SERIES\MV25CU